


Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.0	Intel vPro	Global Educ	Win7 preload
0266-B7U	1x2	Core i5-2400S	4GBx1 1333MHz	320G 7200	DVD±RW	Intel HD	None	None	ES50	vPro	N N	Pro 64
0266-B8U	1x2	Core i5-2500S	4GBx1 1333MHz	500G 7200	DVD±RW	Intel HD	None	None	ES50	vPro	N N	Pro 64

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- These models have a 3-year limited warranty
- These systems are Microsoft Office 2010 Product Key Ready (O10PKR)

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-2400S Processor (4 cores / 4 threads, 2.5GHz, 6MB cache), Turbo Boost 2.0 (3.3GHz), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-2500S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Professional 64 Preloaded applications (only some listed) • Rescue and Recovery™ • ThinkVantage® System Update • ThinkVantage Power Manager • ThinkVantage Toolbox • Norton™ Internet Security 2011 (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Microsoft® Office 2010 preloaded; purchase product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)											
Implementation	Processor in LGA1155 socket																							
Memory	8GB max, PC3-10600 1333MHz DDR3 , two 204-pin SODIMM sockets (notebook)																							
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA) @60Hz</i> None																							
DP dongle	None																							
Disk	SATA 6.0Gb/s 7200 rpm																							
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																							
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1																							
SATA cables	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, one SATA 3.0Gb/s connector, and one eSATA connector on planar																							
eSATA port	None																							
Media reader	None																							
Chipset	Intel Q67 Express Chipset Platform Controller Hub [PCH] (PCI Express® 2.0 x1, ethernet MAC, PCI, and USB), SMSC® 5627P Super I/O																							
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																							
Rear ports	Six USB 2.0, ethernet (RJ-45), VGA DB-15, DisplayPort																							
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																							
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																							
Speaker	Internal speaker for business audio																							
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																							
Intel AMT	Intel Active Management Technology 7.1 (Intel AMT 7.1)																							
Modem	None																							
Security chip	STMicroelectronics ST19NP18 Trusted Platform Module (TPM), TCG 1.2-compliant																							
Mouse	Enhanced Optical USB Mouse, 1000 dpi, black, Lenovo® logo																							
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo																							
Floor Stand	None																							
Power supply	150 watts AC/DC adapter, autosensing, 87% PSU																							
Machine	• Business black color; metal case • 10.8" W X 9.4" D X 3.1" H • 275mm W X 238mm D X 79mm H • 9.2 lb (4.2 kg) in maximum configuration • Hinged toolless cover for easy serviceability • Toolless disk and optical drive removal																							
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk																							
Slot	Slot 1: Low Profile, 32-bit PCI 2.3																							
																								
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																							